ANNUAL SYSTEM OPERATION & MAINTENANCE CHECKLIST

School Name								
Date of Inspection	Voltage/Phas	oltage/PhaseDateInstalled						
Type of Pole								
Inspected By								
mspected by			Oontdot		Nee OK Rep	ds	N/A	No
Lighting Performance Tes	ting							
Check with the AD and Staff to s	ee if there are any concer	ns regarding field (po	le, electrical or lighti	ng)				
Average maintained footcandles	meet guidelines							
Uniformities meet guidelines								
Service Entrance, Poles, a	and Distribution Box	es						
Warning Stickers, wiring diagram	us circuit labals should be	nosted and legible *						
Snap all breakers on and off seve is not recommended due to reduce of arc flash is increased as break A Arc Flash * Check fuses for continuity	eral times to ensure firm c cing the effectiveness of th	ontact. Utilizing break ie devices for overcui	ers for on/off contro rent protection. Also	o, risk				
Insulation around wiring should s	how no signs of deteriora	tion *						
Wiring should show no heat disco								
Signs of wear should be replaced								
Bare wires and exposed connect		vith insulated covering	*					
Are the panels appropriately lock			3					
Are the pariets appropriately lock								
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present?		t poles. The grounding	ig systems are requi	ired to				
Check all grounding connections comply with NFPA 70. *	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a	ls and are they sized by measuring resista second ground rod	properly? nce to ground. Whic	h for a				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in garden to the grounding component and the standard single rod it should be 25 ohms completed.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a	ls and are they sized by measuring resista second ground rod	properly? nce to ground. Whic	h for a				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in g. 3. Are the grounding components. 4. Is the resistance level satisfact single rod it should be 25 ohms or requirement for minimum resistant. Pole Structures Wood poles checked for leaning.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer	ls and are they sized by measuring resista a second ground rod are installed.	properly? nce to ground. Whic	h for a				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 4. Is the resistance level satisfact single rod it should be 25 ohms or requirement for minimum resistant. Pole Structures Wood poles checked for leaning.	good condition? s from acceptable materia tory? This can be verified roless. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmen	ls and are they sized by measuring resista is second ground rod s are installed.	properly? nce to ground. Whic shall be added. Ther	h for a				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a component of the connections in a connection of the co	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer lust below ground level, w	ls and are they sized by measuring resista is second ground rod s are installed.	properly? nce to ground. Whic shall be added. Ther	h for a				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a same and the grounding component. 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for decay. Steel anchor bolt poles checked.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer Just below ground level, w for signs of corrosion *	ls and are they sized by measuring resista a second ground rod sare installed. In the following second of the seco	properly? nce to ground. Whic shall be added. Ther	h for a				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a component of the connections in a connection of the co	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer Just below ground level, w for signs of corrosion * for proper drainage in gro	ls and are they sized by measuring resista a second ground rod are installed. In the of luminaires	properly? nce to ground. Whic shall be added. Ther	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 3. Are the grounding component. 4. Is the resistance level satisfact single rod it should be 25 ohms or requirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for twisting. Wood poles checked for decay. Steel anchor bolt poles checked. Steel anchor bolt poles checked. Direct burial steel poles checked or pitting of the galvanized protect.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer dust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident	ls and are they sized by measuring resista a second ground rod are installed. Int of luminaires oodpecker holes etc. ut at base g above/below grade	properly? nce to ground. Whice shall be added. Ther * at base to ensure no	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 4. Is the resistance level satisfact single rod it should be 25 ohms or requirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for twisting. Wood poles checked for decay. Steel anchor bolt poles checked. Steel anchor bolt poles checked or pitting of the galvanized protect.	good condition? s from acceptable materia tory? This can be verified roless. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer lust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside	ls and are they sized by measuring resista is second ground rod sare installed. In the of luminaires of luminaires of luminaires of gabove/below grade pole and corrosion at	properly? nce to ground. Whice shall be added. Ther * at base to ensure no	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 3. Are the grounding component. 4. Is the resistance level satisfact single rod it should be 25 ohms or requirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for twisting. Wood poles checked for decay. Steel anchor bolt poles checked. Steel anchor bolt poles checked. Direct burial steel poles checked or pitting of the galvanized protect.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer Just below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering	ls and are they sized by measuring resista is second ground rod sare installed. In the of luminaires of luminaires of luminaires of gabove/below grade pole and corrosion at	properly? nce to ground. Whice shall be added. Ther * at base to ensure no	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in g. 3. Are the grounding components. 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for twisting. Wood poles checked for decay. Steel anchor bolt poles checked. Steel anchor bolt poles checked. Direct burial steel poles checked. Direct burial steel poles checked. Direct burial steel poles checked.	good condition? s from acceptable materia tory? This can be verified roless. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer lust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering check for looseness	ls and are they sized by measuring resista is second ground rod sare installed. In the of luminaires of luminaires of luminaires of gabove/below grade pole and corrosion at	properly? nce to ground. Whice shall be added. Ther * at base to ensure no	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in g. 3. Are the grounding components. 4. Is the resistance level satisfact single rod it should be 25 ohms or requirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for decay. Steel anchor bolt poles checked. Steel anchor bolt poles checked or pitting of the galvanized protect burial steel poles checked. Direct burial steel poles checked.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer dust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering check for looseness ss covers in place *	ls and are they sized by measuring resista a second ground rod sare installed. In the of luminaires of luminaires of luminaires odpecker holes etc. In the odpecker holes etc.	properly? nce to ground. Whice shall be added. There * at base to ensure not ound base of pole	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 4. Is the resistance level satisfact single rod it should be 25 ohms or requirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for twisting. Wood poles checked for decay. Steel anchor bolt poles checked. Steel anchor bolt poles checked or pitting of the galvanized protect. Direct burial steel poles checked. Direct burial steel poles checked. Pull on conduits in hand holes to Check for all pole electrical access.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering check for looseness ss covers in place * uit to be in good shape, n	ls and are they sized by measuring resista a second ground rod sare installed. In the of luminaires of luminaires of luminaires odpecker holes etc. In the odpecker holes etc.	properly? nce to ground. Whice shall be added. There * at base to ensure not ound base of pole	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for twisting. Wood poles checked for decay. Steel anchor bolt poles checked. Steel anchor bolt poles checked or pitting of the galvanized protect. Direct burial steel poles checked. Direct burial steel poles checked. Pull on conduits in hand holes to Check for all pole electrical accest. Check for other visible signs of d. Check any pole climbing equipment.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer dust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering check for looseness ss covers in place * uit to be in good shape, no eterioration? Specify * ent for proper attachment,	Is and are they sized by measuring resista a second ground rod are installed. In the of luminaires	properly? nce to ground. Whice shall be added. There * at base to ensure not ound base of pole *	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 4. Is the resistance level satisfactions in a grounding component. 5. Are the grounding component. 6. Is the resistance level satisfactions in a grounding component. 7. Is the resistance level satisfaction in a grounding rod it should be 25 ohms or requirement for minimum resistance. 8. Pole Structures 8. Wood poles checked for leaning. 9. Wood poles checked for twisting. 9. Wood poles checked for decay. 9. Steel anchor bolt poles checked. 9. Steel anchor bolt poles checked. 9. Steel anchor bolt poles checked. 9. Direct burial steel poles checked. 9. Direct burial steel poles checked. 10. Direct burial steel poles checked. 11. Direct burial steel poles checked. 12. Direct burial steel poles checked. 13. Direct burial steel poles checked. 14. Direct burial steel poles checked. 15. Direct burial steel poles checked. 16. Direct burial steel poles checked. 17. Direct burial steel poles checked. 18. Direct burial steel poles checked.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer dust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering check for looseness ss covers in place * uit to be in good shape, no eterioration? Specify * ent for proper attachment,	Is and are they sized by measuring resista a second ground rod are installed. In the of luminaires	properly? nce to ground. Whice shall be added. There * at base to ensure not ound base of pole *	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 3. Are the grounding component. 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for decay. Steel anchor bolt poles checked: Steel anchor bolt poles checked: Direct burial steel poles checked: Check for all pole electrical access. Check for all external cable cond. Check for other visible signs of d. Check any pole climbing equipm. Check to make sure trees are no.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer Just below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering ston is evident for water/moisture inside for proper mastic covering check for looseness ss covers in place * uit to be in good shape, no eterioration? Specify * ent for proper attachment, t encroaching on the pole	Is and are they sized by measuring resista a second ground rod are installed. In of luminaires are odpecker holes etc. In at the base are grapher and corrosion are grapher	properly? nce to ground. Whice shall be added. There * at base to ensure not ound base of pole *	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in grounding components. 3. Are the grounding components. 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for decay. Steel anchor bolt poles checked. Direct burial steel poles checked. Check for all pole electrical access. Check for all external cable cond. Check for other visible signs of d. Check any pole climbing equipmed. Check to make sure trees are no.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer Just below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering stion is evident for water/moisture inside for proper mastic covering check for looseness as covers in place * uit to be in good shape, in eterioration? Specify * ent for proper attachment, t encroaching on the pole	Is and are they sized by measuring resista a second ground rod are installed. In of luminaires are odpecker holes etc. In at the base are grapher and corrosion are grapher	properly? nce to ground. Whice shall be added. There * at base to ensure not ound base of pole *	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in grounding components. 3. Are the grounding components. 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for decay. Steel anchor bolt poles checked. Direct burial steel poles checked. Check for all pole electrical access. Check for all external cable cond. Check for other visible signs of d. Check any pole climbing equipm. Check to make sure trees are no. Luminaires Check for broken or missing lens.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer Just below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering theck for looseness as covers in place * uit to be in good shape, in eterioration? Specify * ent for proper attachment, t encroaching on the pole lenses, or water damage es, replace as needed	Is and are they sized by measuring resista a second ground rod are installed. In of luminaires of the foliation of the folia	properly? nce to ground. Whice shall be added. There at base to ensure not ound base of pole to ound base of pole to ound base of pole to ound base of pole	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in grounding components. 3. Are the grounding components. 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for decay. Steel anchor bolt poles checked. Direct burial steel poles checked. Check for all pole electrical access. Check for all external cable cond. Check for other visible signs of d. Check any pole climbing equipmed. Check to make sure trees are no.	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer Just below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering check for looseness as covers in place * uit to be in good shape, ne eterioration? Specify * ent for proper attachment, t encroaching on the pole lenses, or water damage less, replace as needed g. Troubleshoot and repa	Is and are they sized by measuring resista a second ground rod are installed. In of luminaires of the foliation of the folia	properly? nce to ground. Whice shall be added. There at base to ensure not ound base of pole to ound base of pole to ound base of pole to ound base of pole	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in g. 3. Are the grounding components 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistance. Pole Structures Wood poles checked for leaning Wood poles checked for twisting Wood poles checked for decay. Steel anchor bolt poles checked Direct burial steel poles checked or pitting of the galvanized protect Direct burial steel poles checked Direct burial steel poles checked Pull on conduits in hand holes to Check for all external cable cond Check for other visible signs of d Check any pole climbing equipm. Check to make sure trees are no Luminaires Check for luminaires not operating company the conduction of	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer Just below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering check for looseness as covers in place * uit to be in good shape, ne eterioration? Specify * ent for proper attachment, t encroaching on the pole lenses, or water damage es, replace as needed ng. Troubleshoot and repa r signs of deterioration	Is and are they sized by measuring resista a second ground rod are installed. In the of luminaires of the odd	properly? nce to ground. Whice shall be added. There at base to ensure not ound base of pole to ound base of pole to ound base of pole to ound base of pole	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in g. 3. Are the grounding component 4. Is the resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistance level satisfact single rod it should be 25 ohms crequirement for minimum resistance. Pole Structures Wood poles checked for leaning Wood poles checked for twisting Wood poles checked for decay. Steel anchor bolt poles checked Steel anchor bolt poles checked or pitting of the galvanized protect Direct burial steel poles checked Direct burial steel poles checked Pull on conduits in hand holes to Check for all external cable cond Check for other visible signs of d Check any pole climbing equipm. Check to make sure trees are no Check for broken or missing lens Check for luminaires not operating Visually inspect ballast/drivers for the company of the protect of the conduction of the protect of the protect of the conduction of the protect	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer and resulting misalignmer dust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering ction is evident for water/moisture inside for proper mastic covering check for looseness as covers in place * uit to be in good shape, ne eterioration? Specify * ent for proper attachment, t encroaching on the pole lenses, or water damage es, replace as needed ag. Troubleshoot and repa or signs of deterioration alignment (visual and light	Is and are they sized by measuring resista a second ground rod are installed. In the of luminaires	properly? nce to ground. Whice shall be added. There at base to ensure not ound base of pole to ound base of pole to ound base of pole to ound base of pole	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component. 4. Is the resistance level satisfacting rod it should be 25 ohms crequirement for minimum resistant. Pole Structures Wood poles checked for leaning. Wood poles checked for twisting. Wood poles checked for decay. Steel anchor bolt poles checked or pitting of the galvanized protect. Direct burial steel poles checked or pitting of the galvanized protect. Direct burial steel poles checked. Pull on conduits in hand holes to Check for all pole electrical access. Check for all external cable cond. Check for other visible signs of d. Check any pole climbing equipm. Check to make sure trees are nother than the conduction of t	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer and resulting misalignmer dust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering tion is evident for water/moisture inside for proper mastic covering check for looseness as covers in place * uit to be in good shape, ne eterioration? Specify * ent for proper attachment, t encroaching on the pole lenses, or water damage tes, replace as needed ag. Troubleshoot and repa or signs of deterioration alignment (visual and light uld show no signs of wear	Is and are they sized by measuring resista a second ground rod are installed. In the of luminaires	properly? nce to ground. Whice shall be added. There at base to ensure not ound base of pole to ound base of pole to ound base of pole to ound base of pole	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component or the property of the provided pr	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer and resulting misalignmer dust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering cition is evident for water/moisture inside for proper mastic covering check for looseness as covers in place * uit to be in good shape, ne eterioration? Specify * ent for proper attachment, t encroaching on the pole lenses, or water damage es, replace as needed ng. Troubleshoot and repa r signs of deterioration alignment (visual and light uld show no signs of wear e secure	Is and are they sized by measuring resista a second ground rod are installed. In the of luminaires of the original of the ori	properly? nce to ground. Whice shall be added. There at base to ensure not ound base of pole to ound base of pole to ound base of pole to ound base of pole	ch for a re is no				
Check all grounding connections comply with NFPA 70. * 1. Is a ground rod present? 2. Are the bolted connections in a grounding component of the provided	good condition? s from acceptable materia tory? This can be verified or less. If it's higher, then a nce value, if two grounds a and resulting misalignmer and resulting misalignmer and resulting misalignmer dust below ground level, w for signs of corrosion * for proper drainage in gro for proper mastic covering cition is evident for water/moisture inside for proper mastic covering check for looseness as covers in place * uit to be in good shape, ne eterioration? Specify * ent for proper attachment, t encroaching on the pole lenses, or water damage es, replace as needed ng. Troubleshoot and repa or signs of deterioration alignment (visual and light uld show no signs of wear es secure of blackening. (metal halid ing. (metal halide)	Is and are they sized by measuring resista a second ground rod are installed. In the of luminaires of the original of the ori	properly? nce to ground. Whice shall be added. There at base to ensure not ound base of pole to ound base of pole to ound base of pole to ound base of pole	ch for a re is no				

Note: Asterisk (*) indicates deficiencies that must be corrected, for safety of participants, prior to hosting playoff events

I have reviewed this completed checklist. Deficits, if any, will be addressed as soon as possible.

School Principal Signature:	Date:
-----------------------------	-------